<u>**In the claims**</u>

Please amend the claims as follows:

1   1.   (Currently amended) An integrated circuit processor comprising:

2   a first instruction buffer corresponding to a primary thread;

3   a second instruction buffer corresponding to a backup thread;

4   a thread switch mechanism that detects when the primary thread stalls, and in

5   response thereto, swaps <u>instructions</u> ~~information~~ stored in the first instruction buffer with

6   <u>instructions</u> ~~information~~ stored in the second instruction buffer.

1   2.   (Original) The integrated circuit processor of claim 1 wherein execution of the

2   backup thread occurs after the swap by executing at least one instruction in the

3   first instruction buffer.

1   3.   (Currently amended) The integrated circuit processor of claim 1 further

2   comprising:

3   a third instruction buffer corresponding to a second primary thread;

4   a fourth instruction buffer corresponding to a second backup thread;

5   wherein the thread swap mechanism further detects when the second primary

6   thread stalls, and in response thereto, swaps <u>instructions</u> ~~information~~ stored in the third

7   instruction buffer with <u>instructions</u> ~~information~~ stored in the fourth instruction buffer.

1   4.   (Original) The integrated circuit processor of claim 3 wherein the first and second

2   primary threads simultaneously issue instructions for execution.

1 5.   (Currently amended) An integrated circuit processor comprising:

2   a first primary instruction buffer corresponding to a first primary thread;

3   a second primary instruction buffer corresponding to a second primary thread;

4   wherein the first and second primary threads simultaneously issue instructions for

5 execution;

6   a first backup instruction buffer;

7   a second backup instruction buffer;

8   a thread switch mechanism that detects when one of the first and second threads

9 stalls, and in response thereto, swaps <u>instructions</u> ~~information~~ stored in one of the first

10 and second primary instruction buffers corresponding to the stalled thread with

11 <u>instructions</u> ~~information~~ stored in one of the first and second backup instruction buffers.

1 6.   (Original) The integrated circuit processor of claim 5 wherein the thread switch

2   mechanism:

3   (1) detects when the first primary thread stalls, and in response thereto,

4   swaps the first primary instruction buffer with the first backup instruction buffer;

5   and

6   (2) detects when the second thread stalls, and in response thereto, swaps

7   the second primary instruction buffer with the second backup instruction buffer.

1 7.   (Currently amended) The integrated circuit processor of claim 5 wherein the first

2   and second backup instruction buffers are part of a pool of backup instruction

3   buffers, wherein <u>instructions</u> ~~information~~ in any backup instruction buffer in the

4   pool may be swapped with <u>instructions</u> ~~information~~ in the first primary instruction

5   buffer, and wherein <u>instructions</u> ~~information~~ in any backup instruction buffer in

6   the pool may be swapped with <u>instructions</u> ~~information~~ in the second primary

7   instruction buffer.

1   8.   (Currently amended) An integrated circuit processor comprising:

2   a first primary instruction buffer corresponding to a first primary thread;

3   a second primary instruction buffer corresponding to a second primary thread;

4   wherein the first and second primary threads simultaneously issue instructions for

5   execution;

6   a first backup instruction buffer;

7   a second backup instruction buffer;

8   a thread switch mechanism that detects when the first thread stalls, and in

9   response thereto, <u>swaps instructions stored in the first primary instruction buffer with</u>

10   <u>instructions stored in the first backup instruction buffer, and</u> begins issuing from the first

11   ~~backup~~ <u>primary</u> instruction buffer, and that detects when the second thread stalls, and in

12   response thereto, <u>swaps instructions stored in the second primary instruction buffer with</u>

13   <u>instructions stored in the second backup instruction buffer, and</u> begins issuing from the

14   second ~~backup~~ <u>primary</u> instruction buffer.

1   9.   (Currently amended) A method for switching between a first thread of execution

2   and a second thread of execution in a multithreaded processor, the method

3   comprising the steps of:

4   (A) providing a first instruction buffer corresponding to the first thread;

5   (B) providing a second instruction buffer corresponding to the second thread;

6   (C) swapping <u>instructions</u> ~~information~~ stored in the first instruction buffer with

7 <u>instructions</u> ~~information~~ stored in the second instruction buffer.

1   10.   (Original) The method of claim 9 wherein step (C) is performed when switching

2   between the first thread and the second thread is required.

1   11.   (Original)   The method of claim 9 wherein step (C) is performed when the first

2   thread stalls.

1   12.   (Original)   The method of claim 9 wherein step (C) is performed when the second

2   thread stalls.

1   13.   (Currently amended)   The method of claim 9 further comprising the step of

2   executing the second thread after the swapping of <u>instructions</u> ~~information~~ in step

3   (C) by executing at least one instruction in the first instruction buffer.

1   14.   (Currently amended)   The method of claim 9 further comprising the steps of:

2   (D) providing a third instruction buffer corresponding to a third thread;

3   (E) providing a fourth instruction buffer corresponding to a fourth thread; and

4   (F) swapping <u>instructions</u> ~~information~~ stored in the third instruction buffer with

5 <u>instructions</u> ~~information~~ stored in the fourth instruction buffer.

1   15.   (Original)   The method of claim 14 wherein step (F) is performed when the third

2   thread stalls.

1   16.   (Original)   The method of claim 14 wherein step (F) is performed when the fourth

2   thread stalls.

1   17.   (Original)   The method of claim 14 wherein the first and third threads

2   simultaneously issue instructions for execution.

1   18.   (Currently amended)   A method for switching between first and second threads
2   of execution in a multithreaded processor, the method comprising the steps of:
3   (A) providing a first primary instruction buffer corresponding to the first thread;
4   (B) providing a second primary instruction buffer corresponding to the second
5   thread;
6   (C) providing a first backup instruction buffer corresponding to a first backup
7   thread;
8   (D) providing a second backup instruction buffer corresponding to a second
9   backup thread;
10   (E) simultaneously issuing instructions from the first primary instruction buffer
11   and from the second primary instruction buffer; and
12   (F) detecting when one of the first and second primary threads stalls, and in
13   response thereto, swapping <u>instructions</u> <s>information</s> stored in one of the first and second
14   primary instruction buffers corresponding to the stalled thread with <u>instructions</u>
15   <s>information</s> stored in one of the first and second backup instruction buffers.

1   19.   (Currently amended)   The method of claim 18 wherein step (E) comprises the
2   steps of:
3   (1) detecting when the first primary thread stalls, and in response thereto,
4   swapping information stored in the first primary instruction buffer with
5   information stored in the first backup instruction buffer; and
6   (2) detecting when the second thread stalls, and in response thereto,
7   swapping <u>instructions</u> <s>information</s> stored in the second primary instruction buffer
8   with <u>instructions</u> <s>information</s> stored in the second backup instruction buffer.

1   20.   (Currently amended) The method of claim 18 wherein the first and second

2   backup instruction buffers are part of a pool of backup instruction buffers,

3   wherein <u>instructions</u> ~~information~~ in any backup instruction buffer in the pool may

4   be swapped with <u>instructions</u> ~~information~~ in the first primary instruction buffer,

5   and wherein <u>instructions</u> ~~information~~ in any backup instruction buffer in the pool

6   may be swapped with <u>instructions</u> ~~information~~ in the second primary instruction

7   buffer.

1   21.   (Currently amended) A method for switching between threads of execution in a

2   multithreaded processor, the method comprising the steps of:

3   (A) providing a first primary instruction buffer corresponding to the first thread;

4   (B) providing a second primary instruction buffer corresponding to the second

5 thread;

6   (C) providing a first backup instruction buffer corresponding to a first backup

7 thread;

8   (D) providing a second backup instruction buffer corresponding to a second

9 backup thread;

10   (E) simultaneously issuing instructions from the first primary instruction buffer

11 and from the second primary instruction buffer; and

12   (F) detecting when the first threads stalls, and in response thereto, <u>swapping</u>

13 <u>instructions stored in the first primary instruction buffer with instructions stored in the</u>

14 <u>first backup instruction buffer, and</u> issuing <u>instructions</u> ~~from the first backup instruction~~

15 ~~buffer instead of issuing~~ from the first primary instruction buffer.

1   22.   (Currently amended) The method of claim 21 further comprising the step of

2   (G) detecting when the second thread stalls, and in response thereto, <u>swapping</u>

3 <u>instructions stored in the second primary instruction buffer with instructions stored in the</u>

4 <u>second backup instruction buffer, and</u> issuing from ~~the second backup instruction buffer~~

5 ~~instead of issuing from~~ the second primary instruction buffer.

STATUS OF THE CLAIMS

Claims 1-22 were originally filed in this patent application. In response to the office action dated 03/29/06, a Request for Reconsideration was filed on 06/29/06 that included a declaration under 37 C.F.R. 1.132 to remove the Luick reference as prior art. In the pending office action, claims 1-2 and 9-13 were rejected under 35 U.S.C. §102(b) as being anticipated by U.S. Patent No. 6,348,671 to Doing *et al.* (hereinafter "Doing"). Claims 3-6, 8 and 14-19 were rejected under 35 U.S.C. §103(a) as being unpatentable over Doing in view of U.S. Publication No. 2003/0135711 to Shoemaker *et al.* (hereinafter "Shoemaker"). Claims 7 and 20 were rejected under 35 U.S.C. §103(a) as being unpatentable over Doing in view of Shoemaker and U.S. Patent No. 6,314,511 to Levy *et al.* (hereinafter "Levy"). Claims 21 and 22 were rejected under 35 U.S.C. §103(a) as being unpatentable over Doing and Shoemaker in view of U.S. Patent No. 6,957,326 to Redington. No claim was allowed. Claims 1, 3, 5, 7-9, 13-14, and 18-22 have been amended herein. Claims 1-22 are currently pending.